

#7

# BIOCHIP AND METHOD FOR PRODUCING THE SAME

## BACKGROUND OF THE INVENTION

### Field of the Invention:

5           The present invention relates to a DNA microarray (DNA chip) which specifically reacts with a biochemical specimen and which is used for inspection equipment represented, for example, by a biochip to be used in order to obtain information on the structure and the function of the specimen, preferably in which several hundreds to several ten thousands kinds of captures, especially DNA fragments or the like for capturing the specimen are aligned and fixed at a high density as minute spots on a base plate such as a microscopic slide glass. The present invention also relates to a method for producing the same.

### Description of the Related Art:

          The method for analyzing the gene structure has been remarkably progressed in recent years. A large number of gene structures represented by those of human gene have been clarified. The analysis of the gene structure as described above uses a DNA microarray (DNA chip) in which several hundreds to several ten thousands kinds of DNA fragments or the like are aligned and fixed as minute spots on a base plate such as a microscopic slide glass.

20           Those widely used as the method for forming the minute spots for the production of the DNA microarray are generally based on a system such as the QUILL system, the pin & ring

system, and the spring pin system in which a sample solution is stamped onto the base plate by using a pin.

Even when any one of the foregoing methods is adopted, it is important to suppress the dispersion of the volume and the shape of each of the minute spots to be low so that the distance between the respective minute spots is maintained to be constant. Further, it is necessary that the capture (corresponding to the DNA fragment or the like in the case of the DNA microarray), which specifically reacts with a specimen in the minute spot formed on the base plate and which is used to obtain information on the structure and the function of the specimen, is reliably immobilized on the base plate.

On the other hand, in order to realize a higher density, it is also greatly expected to develop a new method which is excellent in productivity and in which the shape control performance for the minute spot is satisfactory.

In the conventional production of the biochip, when the sample containing DNA fragments or the like is dropped onto the base plate to form minute spots, or when the chip is dealt with or treated thereafter, the minute spots may be peeled off. When the DNA fragments or the like are immobilized on the base plate in the DNA microarray, several techniques are adopted, in which a functional group to facilitate immobilization is affixed to the DNA fragments themselves, or the surface of the base plate is coated with a functional group layer. However, even when such a

technique is adopted, the adopted technique is insufficient to avoid the peeling off of the minute spots.

Further, a technique is also adopted, in which a hydrophilic polymer or the like is dissolved in a sample containing DNA fragments or the like to reinforce the immobilization of the DNA fragment or the like onto the base plate. However, the cost may be increased, because it is necessary to perform the step to mix the sample and an immobilization-reinforcing solution, and it is also necessary to use a large amount of the immobilization-reinforcing solution. Further, when such an immobilization-reinforcing solution and samples are previously mixed and supplied onto the base plate, it is necessary to consider the compatibility and the conformability between one type of the immobilization-reinforcing solution and the samples of several thousands or more types. The selection of the material for the immobilization-reinforcing solution has been restricted.

Further, the sample containing the immobilization-reinforcing solution has to be supplied onto the base plate in accordance with the conventional method. Therefore, a drawback arises in that only the immobilization-reinforcing solution, which has physical properties to be successfully supplied by the supply method, can be used.

Specifically, in the method for mechanically forming spots based on the use of a pin as a general method for producing the DNA microarray, the sample containing the

immobilization-reinforcing solution must be a sample which adheres to the pin, because the sample is physically retained (adhered) onto the pin to move (supply) the sample onto the base plate. Further, it is necessary that the amount of adhesion is made uniform as far as possible for all cases of DNA fragments or the like of several thousands or more types. Therefore, the selection of the immobilization-reinforcing agent to be mixed with DNA fragments or the like has been extremely restricted.

On the other hand, an ink-jet type spotting method, which is one of non-contact type spotting methods, is known as a method for accurately forming minute spots. A micropipette in which a piezoelectric/electrostrictive element is used as a micropump and a dispenser which is based on the use of the same have been developed and practically used as an apparatus for accurately dispensing a minute amount of biological sample based on the use of the ink-jet type spotting method.

In the non-contact type spotting method, a biological sample, which contains, for example, DNA fragments, nucleic acids, and amino acids, is discharged as minute droplets to the space so that the sample is dropped onto a base plate such as a slide glass.

However, in this method, the minute droplets of the biological samples having relatively high viscosities, which are of several hundreds to several ten thousands types with delicate differences in physical properties of the

10  
20  
30  
40  
50  
60  
70  
80  
90  
100  
110  
120  
130  
140  
150  
160  
170  
180  
190  
200  
210  
220  
230  
240  
250  
260  
270  
280  
290  
300  
310  
320  
330  
340  
350  
360  
370  
380  
390  
400  
410  
420  
430  
440  
450  
460  
470  
480  
490  
500  
510  
520  
530  
540  
550  
560  
570  
580  
590  
600  
610  
620  
630  
640  
650  
660  
670  
680  
690  
700  
710  
720  
730  
740  
750  
760  
770  
780  
790  
800  
810  
820  
830  
840  
850  
860  
870  
880  
890  
900  
910  
920  
930  
940  
950  
960  
970  
980  
990  
1000

5  
respective solutions, are discharged to the space so that the minute droplets are dropped onto the slide glass base plate. Therefore, the so-called satellites (splashed droplets finer than objective discharged droplets) tend to appear during the discharge in addition to the objective droplets (objective discharged droplets). The satellites are dropped onto the base plate, resulting in problems on quality of the obtained product, for example, such that spots are formed at portions other than original spot formation positions, and it is impossible to maintain constant spacing distances between the minute spots to cause any contamination due to the mixing with each other.

The so-called satellites as described above are not caused at the early stage of the operation of the dispenser in some cases, but the satellites occur after continuing the operation for a certain period of time. An extremely troublesome problem arises in this way in view of the management of production steps. When the discharge speed of the droplets is large, the momentum of the droplets is large upon the dropping onto the slide glass base plate, resulting in a problem such that splashes (mists) are generated to form unnecessary spots (also referred to as "satellites") around the genuine spot.

25  
In order to avoid the occurrence of the so-called satellites as described above, the discharge speed may be decreased. However, if the discharge speed is decreased, the discharge operation is unstable.

When the method, in which the hydrophilic polymer or the like is dissolved in the sample containing DNA fragments or the like to reinforce the immobilization of the DNA fragments or the like onto the base plate as described above, is adopted for the ink-jet type spotting method, the sample solution is discharged onto the base plate through a discharge nozzle. However, the solidification of the sample solution may be advanced during the process for discharging the sample solution onto the base plate, resulting in discharge failure. Especially, when an immobilization solution having a high viscosity is mixed with the sample to effect the discharge, any discharge defect is caused by the drying and solidification of the sample solution in the vicinity of the discharge nozzle.

Further, when it is intended to actually obtain information on the structure or the function of a specimen, the specimen is nonspecifically bound to the base plate other than the spots. Conventionally, in order to avoid such a phenomenon, a blocking treatment (treatment to avoid any binding of the specimen to portions other than portions at which the spots are formed on the base plate) is performed after forming the spots on the base plate.

However, most of captures supplied onto the base plate may flow out during the blocking treatment.

Further, the blocking treatment may be incomplete and the S/N ratio of the signal from the spot is deteriorated.

## SUMMARY OF THE INVENTION

The present invention has been made taking the foregoing problems into consideration, an object of which is to provide a biochip and a method for producing the same in which a high quality biochip having a high S/N ratio of a signal from a spot is successfully produced without any missing of minute spot of a sample containing DNA fragments or the like, making it possible to simplify production steps, reduce the cost, and improve the yield.

According to the present invention, there is provided a biochip comprising a large number of spots based on capture solutions, the spots being arranged on a base plate by supplying, onto the base plate, a plurality of types of the capture solutions to be used to specifically react with a specimen in order to obtain information on a structure or a function of the specimen; wherein a first substance, which acts on immobilization of the captures onto the base plate, is formed at least at portions at which the spots are to be formed on the base plate. The solution sample containing the capture herein refers to a solution obtained by dissolving or dispersing the capture in a liquid, which is also referred to as "sample containing the capture solution".

Accordingly, the capture is strongly immobilized onto the base plate. It is possible to prevent the capture from being peeled off, for example, due to the blocking treatment. The first substance, which acts on the

immobilization, may be an immobilization solution for immobilizing the captures onto the base plate, or an immobilization-reinforcing solution for reinforcing the immobilization.

5           The biochip according to the present invention resides in a biochip comprising a large number of spots based on samples containing captures, the spots being arranged on a base plate by supplying, onto the base plate, a plurality of types of the samples containing the captures to be used to specifically react with a specimen in order to obtain information on a structure or a function of the specimen; wherein the first substance, which acts on the immobilization of the captures onto the base plate, is formed at least at the portions at which the spots are to be formed on the base plate, and a second substance, which inhibits the immobilization of at least the captures onto the base plate, is formed at parts other than the portions at which the spots are to be formed.

10  
20  
25           Accordingly, the shape and the arrangement form of the spots are determined by the shape of the parts at which the second substance is not formed. Therefore, for example, inconveniences, in which the arrangement spacing between the spots is dispersed and/or the spots are putted close to one another, are avoided when the samples are supplied onto the base plate. If the samples cannot be supplied to prescribed positions, the samples are prevented from contacting with the base plate owing to the presence of the second



substance. Therefore, no contamination source is brought about thereby. Thus, the biochip is obtained, which is excellent in reliability, reproducibility, and quantitative performance when the analysis is performed.

5 When the sample is supplied in accordance with the ink-jet system, splashes or mists are often generated due to the satellite phenomenon caused when the sample is discharged. Such splashes or mists are prevented from contacting with the base plate owing to the presence of the second substance. Therefore, the problem of satellites, which has been caused in the ink-jet system, is successfully dissolved.

In other words, according to the present invention, the high quality biochip can be obtained inexpensively.

As for the biochip constructed as described above, it is preferable that the second substance is a substance which inhibits the immobilization of the captures onto the base plate and which inhibits the contact of the specimen with the base plate. In this case, the substance, which inhibits the contact of the specimen with the base plate, has been already present at the parts other than the parts at which the spots are to be formed, before the formation of the spots. Therefore, it is unnecessary to perform the blocking treatment for each of the spots after the formation of the spots. Accordingly, it is possible to reliably obtain a large amount of the capture to be immobilized onto the base plate as compared with an ordinary biochip. As a result,

the sensitivity to the specimen is improved.

It is also preferable that the first substance is formed on an entire surface of the base plate; and the second substance is formed at parts other than the portions at which the spots are to be formed on the first substance formed on the base plate.

Accordingly, the shape of the parts at which the second substance that determines the shape and the arrangement form of the spots is not formed can be prescribed by only the formation of the second substance. Therefore, the biochip, in which the dispersions of the spacing distance between the spots and the individual shapes are suppressed, is realized. As a result, it is possible to perform accurate analysis in which the sensitivity to the specimen is uniform.

According to another aspect of the present invention, there is provided a method for producing a biochip comprising a large number of spots based on capture solutions, the spots being arranged on a base plate by supplying, onto the base plate, a plurality of types of the capture solutions to be used to specifically react with a specimen in order to obtain information on a structure or a function of the specimen; the method comprising the step of supplying a solution sample containing the capture and a solution sample containing no capture separately from each other to produce the biochip. In this process, it is preferable that the solution sample containing the capture is supplied in accordance with an ink-jet system.

The solution sample containing no capture herein refers to the solution in which no capture exists in the liquid, which is also referred to as "sample containing no capture solution".

5           When the sample containing the capture solution and the sample containing no capture solution are supplied separately from each other, the sample containing no capture solution can be selected only in view of the property that the sample containing no capture solution has the performance to reliably immobilize and retain the capture on the base plate, which is preferred. Further, the sample containing the capture solution can be supplied by a supply means which is distinct from a supply means for the sample containing no capture solution. Therefore, it is possible to employ a supply method which is optimum for each of the solutions.

As a result, the following advantage is obtained. That is, the samples containing the capture solutions of several hundreds types or more are sometimes used, while one type of the sample containing no capture solution is usually used in many cases. In such circumstances, it is possible to adopt the means with which a large amount of the sample can be treated conveniently and inexpensively, as the supply means for the sample containing no capture solution.

20           When the ink-jet system is used as the supply means for the sample containing the capture solution, a minute amount of the sample containing the capture solution can be

accurately supplied onto the base plate. The ink-jet system is a non-contact type liquid supply system. Therefore, the ink-jet system is most appropriate when one spot is formed by supplying two or more types of solutions of the sample containing the capture solution and the sample containing no capture solution, for the following reason.

That is, except for the case of certain limited research experiments, a plurality of biochips are usually produced at once. The sample containing the identical capture solution is supplied a plurality of times to a plurality of base plates. In such a situation, for example, if the sample is supplied while making contact with the base plate as in the pin system, the sample containing the capture solution and the sample containing no capture solution are mixed with each other at the pin tip. The mixing rate is changed every time when the supply is performed. As a result, such a procedure causes any dispersion of the amount of capture supplied to each of the spots of each of the biochips. Such a problem is completely excluded by adopting the non-contact type liquid supply system such as the ink-jet system.

Further, in the ink-jet system, for example, the discharge amount and the momentum of discharge (discharge speed) can be accurately controlled electrically. Therefore, it is also possible to intentionally change the ratio between the sample containing the capture solution and the sample containing no capture solution for each spot.

The ink-jet system is advantageous to improve the quality.

Further, in the present invention, it is preferable that the sample containing no capture solution is supplied to the base plate in accordance with an ink-jet system or a screen printing system. When the sample is supplied in accordance with the ink-jet system, then the sample containing no capture solution can be supplied accurately in a minute amount in the same manner as the sample containing the capture solution described above, and the both solutions can be supplied in a well-controlled manner without any dispersion of the mixing rate of the both solutions. Thus, the quality of the biochip is improved.

When the sample is supplied in accordance with the screen printing system, the sample can be supplied inexpensively and quickly in a large amount with sufficient accuracy for the ordinary biochip in which about several thousands of spots are formed per one sheet, although the amount and the position cannot be accurately controlled as compared with the ink-jet system.

The supply of the sample containing no capture solution is not limited to the ink-jet system and the screen printing system. The sample may be supplied, for example, in accordance with the dipping system or the spray system by effecting the patterning with a mask, if necessary.

In this case, the sample containing no capture solution may be an immobilization solution for immobilizing the sample containing the capture solution onto the base plate,

or an immobilization-reinforcing solution for reinforcing immobilization.

Accordingly, at first, when the sample containing the capture is supplied, the immobilization solution is also supplied. Therefore, it is unnecessary to previously supply (or coat in common cases) the immobilization solution onto the base plate. It is possible to prevent the increase in cost of the base plate beforehand. Further, both of the supply of the immobilization solution and the supply of the sample containing the capture are performed within a relatively short period of time. Therefore, it is possible to suppress the occurrence of dispersion of the quality of the biochip due to the time-dependent change of the immobilization solution, unlike a case in which the immobilization solution is previously supplied onto the base plate.

Further, it is unnecessary to perform the step of mixing the sample and the immobilization-reinforcing solution, because the sample and the immobilization-reinforcing solution are supplied separately from each other. Further, it is enough to use a slight amount of the immobilization-reinforcing solution which is necessary to reinforce the immobilization of the minute amount of sample supplied onto the base plate. Therefore, it is possible to greatly decrease the amount of the immobilization-reinforcing solution. This procedure is advantageous to simplify the production steps and reduce the cost.

When the ink-jet system is adopted, it is unnecessary to conform the nozzle for supplying the immobilization solution or the immobilization-reinforcing solution to the supply specification for the sample containing the capture.

5 The nozzle can be designed exclusively (for example, to have a structure which is hardly dried). Thus, it is possible to improve the degree of freedom of the design.

Further, even when the immobilization solution or the immobilization-reinforcing solution is a liquid which is apt to be dried or solidified, the sample is not solidified during the supply of the sample containing the capture.

10 Therefore, it is possible to supply the sample with enough time margin. Therefore, the sample and the immobilization solution can be supplied while considering, for example, the positioning for the supply portion including the capture, the supply timing depending on the type of the sample, and the supply amount. It is possible to improve the quality of the biochip and improve the yield.

Especially, it is preferable that the immobilization solution or the immobilization-reinforcing solution is a solution with which immobilization or immobilization reinforcement is advanced by mixing the immobilization solution or the immobilization-reinforcing solution with the sample containing the capture. In this case, the sample and

20 the immobilization solution can be supplied with more sufficient time margin. This procedure contributes to the improvement in yield.

When the sample containing the capture and the immobilization solution or the immobilization-reinforcing solution are supplied separately from each other, then the immobilization solution or the immobilization-reinforcing solution may be supplied onto the base plate, and then the sample containing the capture may be supplied to parts to which the immobilization solution or the immobilization-reinforcing solution has been supplied. Inversely, the sample containing the capture may be supplied onto the base plate, and then the immobilization solution or the immobilization-reinforcing solution may be supplied to parts to which the sample containing the capture has been supplied. Alternatively, the both may be supplied substantially simultaneously.

When the immobilization solution or the immobilization-reinforcing solution is previously supplied onto the base plate, the solution physically intervenes between the capture and the base plate. Thus, the immobilization is further strengthened. However, the immobilization-reinforcing agent persistently reinforces the immobilization. Therefore, it is preferable to use those which exert less influence to inhibit the physical contact between the capture and the base plate or between the capture and the immobilization solution on the base plate. It is recommended to use a polymer type substance having a structure including many three-dimensional interstices.

When the immobilization solution or the immobilization-



reinforcing solution is supplied after the sample containing the capture is supplied, the solution is consequently supplied onto the portion to which the sample containing the capture has been accurately supplied beforehand. It is unnecessary to strictly prescribe the positioning accuracy when the immobilization solution or the immobilization-reinforcing solution is supplied. Therefore, it is possible to increase the yield inexpensively. In this case, it is required to use the immobilization solution or the immobilization-reinforcing solution having a structure and a thickness so that the action of the capture to capture the specimen is not inhibited.

Further, when the sample containing the capture and the immobilization solution or the immobilization-reinforcing solution are supplied substantially simultaneously, the supply time can be shortened, which is preferred. This procedure can be achieved in accordance with the ink-jet system which is a non-contact type supply system.

It is preferable that the captures are nucleic acids. Further, it is preferable that the nucleic acid is DNA and/or fragment thereof or amplified product thereof; cDNA and/or fragment thereof or amplified product thereof; RNA or antisense RNA and/or fragment thereof or amplified product thereof; chemically synthesized DNA or amplified product thereof; or chemically synthesized RNA or amplified product thereof.

It is preferable that the captures are proteins.

Further, it is preferable that the protein is antigen, antibody, lectin, adhesin, receptor for physiologically active substance, or peptide.

5 It is preferable that the immobilization solution is a solution of chemical substance having positive charge, and the capture is immobilized by means of ionic bond. That is, the following forms are preferred: the chemical substance is a silane coupling agent such as  $\gamma$ -aminopropyltriethoxysilane, poly-L-lysine, or polyalkylamine; or the immobilization solution includes a chemical substance for chemically modifying a base plate surface, and a functional group introduced into the base plate surface and a functional group introduced by modifying the capture are subjected to a chemical reaction to immobilize the capture onto the base plate by means of covalent bond; i.e., the chemical reaction is a reaction of amino group and aldehyde group, a reaction of amino group and N-hydroxysuccinimido group, a reaction of amino group and carboxyl group, a reaction of amino group and epoxy group, or a reaction of thiol group and epoxy group. 20 Alternatively, the following forms are preferred: the immobilization solution generates affinity bond or hydrogen bond for the capture with respect to the base plate; i.e., the immobilization solution includes avidin, streptavidin, protamine, or histone. Further alternatively, the following forms are preferred: the immobilization solution generates hydrophobic bond for the capture with respect to the base 25

plate; i.e., the immobilization solution is a solution containing hydrophobic group such as phenyl group of hydrophobic substance such as polystyrene and alkyl group of alkylbenzene or the like.

Further, the following forms are preferred: the immobilization-reinforcing solution includes a water-retentive substance; i.e., the water-retentive substance is colominic acid, hyaluronic acid, or mixture of colominic acid and hyaluronic acid. Alternatively, the following forms are preferred: the immobilization-reinforcing solution includes a high-molecular substance; i.e., the high-molecular substance is acidic polymer such as CM-cellulose, nitrocellulose, polyacrylic acid, and alginic acid; basic polymer such as polyethyleneimine and polyacrylamide; neutral polymer such as methyl cellulose, polyethylene glycol, and polypropylene glycol; or protein such as BSA, egg albumin, and lysozyme.

When the substances of the capture, the immobilization solution, and the immobilization-reinforcing solution are combined as described above, the immobilization of the capture onto the base plate is more strengthened. Further, when this feature is combined with the method in which the solution containing the capture and the solution containing no capture, i.e., the immobilization solution or the immobilization-reinforcing solution are supplied onto the base plate separately from each other in accordance with the basic concept of the present invention, the immobilization

proceeds in a form in which the orientation is uniformized for the captures, i.e., the captures are spread over the base plate three-dimensionally. It is easy for the capture to capture the specimen. As a result, the quality of the biochip is improved.

Further, when the solutions are supplied separately from each other, the functions of the immobilization solution and the immobilization-reinforcing solution are prevented from deterioration which would be otherwise caused by any influence exerted by drying or the like brought about by being left to stand in the atmospheric air. Accordingly, the solutions are supplied onto the base plate while retaining the original functions of the foregoing substances, which is preferred.

Further, when the water-retentive substance is used for the immobilization-reinforcing solution, the immobilization reaction for the capture to be immobilized on the base plate can be sufficiently advanced in an enough period of time by retaining water in the spots, which is preferred.

Further, when the high-molecular substance is used for the immobilization-reinforcing solution, then the capture is freely movable in the immobilization-reinforcing solution, and the immobilization or the capture of the specimen by the capture is not inhibited, which is preferred.

Especially, the capture is preferably prepared by performing the steps of PCR-amplifying DNA fragments to prepare PCR product, drying the PCR product to obtain DNA

powder, and dissolving the DNA powder in a buffer solution. When the PCR amplification step is performed, a variety of functional groups to facilitate immobilization can be added to DNA fragments, which is preferred for the present invention.

Preferably, the present invention further comprises preparing a jig to which a plurality of the base plates are set, wherein the sample containing the capture solution and the sample containing no capture solution are supplied in a state in which the base plates are fixed on the jig. The setting of the base plates is not subjected to resetting every time when the solution is supplied. Accordingly, it is possible to reduce the production cost. On the other hand, an advantage is simultaneously obtained such that it is possible to reduce the discrepancy of the positions to which two solutions are to be supplied.

Further, the method for producing the biochip according to the present invention has such a feature that an area, in which the sample containing no capture solution is supplied onto the base plate, is substantially the same as an area to which the sample containing the capture solution is supplied, or an area which includes the area to which the sample containing the capture solution is supplied, the area having a substantially circular shape.

Accordingly, the shape of the spot, in which each of the captures of the biochip exists, is determined by the spot shape of one type of the sample containing no capture

solution. Therefore, it is possible to eliminate the deviation of the spot shape which would be otherwise caused by the difference in the type of the capture.

The procedure can be successfully managed with one type of supply means (pin or ink-jet discharge unit) as well, because one type of the sample containing no capture solution is supplied. Therefore, it is also possible to eliminate the dispersion of the spot shape which would be otherwise caused by the difference in the supply means. Further, the size of each of the spot shapes of the biochip is determined by the amount of supply of the sample containing no capture, and the amount can be made larger than the amount of supply of the sample containing the capture solution. As a result, it is possible to reduce the amount of supply of the sample containing the capture solution to realize the size of the spot required for the biochip.

In the case of the ordinary method for producing the biochip in the present circumstances, almost all of the amount of the sample containing the capture solution supplied onto the base plate is washed out without being immobilized onto the base plate. On the contrary, in the present invention, the sample containing the capture solution is diffused up to a supply area formed by the sample containing no capture solution. Therefore, the sample is immobilized more efficiently on the base plate. It is possible to decrease the amount of being washed out

without being immobilized.

Further, the production method as described above is preferred when the sample containing the capture solution is supplied in accordance with the ink-jet method. In this procedure, even when satellites are generated when the sample containing the capture solution is supplied as described above, the satellites scarcely arrive at the sample solution area containing no capture. Even if the satellites arrive at the sample solution area containing no capture, the satellites are integrated into the regular sample. As a result, it is possible to avoid almost all of the satellite problem.

This effect is exerted on not only the satellite problem. The same or equivalent effect is preferably exhibited also for the "problem of so-called flight curvature resulting in dispersion of discharge direction" which may be possibly caused in the case of the ink-jet system.

Further, in the present invention, the method for producing the biochip may have such a feature that an area, in which the sample containing no capture solution is supplied onto the base plate, has a size which includes two or more areas to each of which the sample containing the capture solution is supplied. In this case, the sample containing no capture solution is supplied more conveniently.

According to still another aspect of the present

invention, there is provided a method for producing a biochip comprising the steps of providing a first substance which acts on said immobilization of the captures onto said base plate, at portions at which at least the spots are to be formed, and forming a second substance for inhibiting at least immobilization of the captures onto the base plate at parts other than portions at which the spots are to be formed on the base plate provided with the first substance.

Accordingly, the solution containing the capture is subjected to the spotting onto the base plate by using the base plate on which the first substance is formed at the portions to be subjected to the spotting beforehand and the second substance is formed at the portions other than the above. The shape and the arrangement form of the spots are determined by the shape of the parts at which the second substance is not formed. For example, inconveniences, in which the arrangement spacing between the spots is dispersed and the spots are putted close to one another, disappear. Further, when the sample cannot be supplied to the prescribed position, the sample is prevented from contacting with the base plate owing to the presence of the second substance. Therefore, no contamination source is generated. Splashes or mists, which are caused by the satellite phenomenon often caused during the discharge of the sample when the sample is supplied in accordance with the ink-jet system, are prevented from contacting with the base plate owing to the presence of the second substance. Therefore,



it is possible to dissolve the problem of satellite having been hitherto caused by the ink-jet system. The present invention is advantageous as described above. It is possible to produce the high quality biochip. It is possible to simplify the production steps, reduce the cost, and improve the yield.

It is preferable that the production method described above further comprises the steps of forming the first substance at the portions at which at least the spots are to be formed on the base plate; and forming the second substance at the parts other than the portions at which the spots are to be formed on the base plate. When the method comprises the step of forming the first substance and the step of forming the second substance, then the materials can be selected while taking the compatibility of each of the substances into consideration, and the formation timing can be individually adjusted. Thus, it is possible to extract the characteristics of each of the substances to the maximum.

It is also preferable that the production method described above further comprises the steps of forming the first substance on an entire surface of the base plate; and forming the second substance at parts other than the portions at which the spots are to be formed, on the first substance formed on the base plate. When the first substance is formed on the entire surface, it is possible to adopt the steps of mass production in which the cost is

further suppressed.

It is also preferable that the production method described above further comprises the steps of using, as the base plate, a base plate on which the first substance is previously formed at the portions at which the spots are to be formed; and forming the second substance at parts other than the portions at which the spots are to be formed on the base plate.

It is also preferable that the second substance is a substance which inhibits the immobilization of the captures onto the base plate and which inhibits the contact of the specimen with the base plate.

It is also preferable that the sample containing the capture is supplied in accordance with an ink-jet system. In this procedure, the sample can be supplied efficiently at a high speed. Further, the sample is supplied in accordance with the non-contact system in which the supply means makes no contact with the base plate. Therefore, it is possible to avoid such a problem that the second substance, which is previously formed on the base plate, is mixed into the sample supply means to cause the contamination.

When the sample is supplied in accordance with the ink-jet system, the high speed supply can be realized. However, the satellite phenomenon is often caused during the discharge of the sample, and the base plate is polluted in some cases. However, splashes or mists, which are caused by the satellite phenomenon, are prevented from contacting with

the base plate owing to the presence of the second substance. Therefore, the problem of satellite, which has been hitherto caused in the ink-jet system, is successfully dissolved. Therefore, the supply of the sample in accordance with the ink-jet system can be actively facilitated.

It is also preferable in the production method described above that the first step includes a treatment for forming the first substance on the entire surface of the base plate; and the second step includes a treatment for forming the second substance at parts other than the portions at which the spots are to be formed, on the first substance.

In this case, it is also preferable that the second substance is supplied in accordance with an ink-jet system. When the second substance is formed at the parts other than the portions at which the spots are to be formed, it is possible to improve both of the positional accuracy and the thickness accuracy. It is possible to clearly discriminate the shape of the boundary between the parts at which the spots are to be formed and the parts other than the portions at which the spots are to be formed. Further, the second substance can be supplied efficiently without any loss. Therefore, the method contributes to the reduction of the production cost.

It is also preferable that the second substance is formed in accordance with a screen printing method. In this

case, it is possible to shorten the supply time for the second substance to the parts other than the portions at which the spots are to be formed. It is possible to improve the throughput and reduce the number of steps.

5 It is also preferable that the second substance is formed in accordance with a dipping method. In this case, it is also preferable that a resist is formed at the portions at which the spots are to be formed, on the first substance formed on the base plate; the second substance is formed on an entire surface including the resist in accordance with the dipping method; and the resist is subjected to lift-off to form the second substance at parts other than the portions at which the spots are to be formed.

The method based on the dipping is preferably adopted when the second substance has a low viscosity. Also in this case, it is possible to shorten the supply time for the second substance to the parts other than the portions at which the spots are to be formed. It is possible to improve the throughput and reduce the number of steps.

20 When the first substance is a chemical substance having positive charge to act on the immobilization of the captures onto the base plate by means of ionic bond; the second substance is a chemical substance having negative charge.

25 In this case, it is preferable that the first substance includes at least a silane coupling agent such as  $\gamma$ -aminopropyltriethoxysilane, poly-L-lysine, polyethyleneimine, or polyalkylamine; and the second

substance includes at least organic acid such as succinic acid, gluconic acid, glycolic acid, malic acid, and acrylic acid; synthetic high-molecular acid such as polyacrylic acid, polylactic acid, dextran sulfate, and polyglycolic acid; or natural high-molecular acid such as alginic acid, polygalacturonic acid, hyaluronic acid, and chondroitin sulfuric acid.

The combination, in which the first substance is the chemical substance having positive charge and the second substance is the chemical substance having negative charge, is preferably adopted when the capture has negative charge and the immobilization onto the base plate is performed by means of ionic bond. However, when the capture has no negative charge, a combination may be also available, in which the first substance is a chemical substance having negative charge and second substance is a chemical substance having positive charge.

When the first substance is a chemical substance having an active group for modifying a base plate surface to act on the immobilization of the captures onto the base plate by means of covalent bond by effecting a chemical reaction of the active group introduced into the base plate surface and a functional group introduced by modifying the captures; the second substance is a chemical substance having the functional group reactive with the active group.

In this case, the chemical reaction to achieve the covalent bond is a reaction of amino group and aldehyde

group, a reaction of amino group and N-hydroxysuccinimido group, a reaction of amino group and carboxyl group, a reaction of amino group and epoxy group, or a reaction of thiol group and epoxy group.

5 It is preferable that the first substance includes at least a mixture of  $\gamma$ -aminopropyltriethoxysilane and glutaraldehyde, a mixture of  $\gamma$ -aminopropyltriethoxysilane, succinic anhydride, and N-hydroxysuccinimido, a mixture of  $\gamma$ -aminopropyltriethoxysilane and succinic anhydride, epichlorohydrin, or bisoxysilane; and the second substance includes at least amino acid such as glycine, tris having amino group, ethanolamine, cysteine having thiol group, glutathione, or thioglycol.

10  
15  
20  
25 When the first substance is a chemical substance for modifying a base plate surface to act on the immobilization of the captures onto the base plate by means of affinity bond; the second substance is a substance which makes the affinity bond with the chemical substance.

30 In this case, it is preferable that the first substance includes at least avidin, streptavidin, protamine, histone, biotin, antigen, antibody combining protein, or antibody; and the second substance includes at least avidin, streptavidin, biotin, nucleic acid, antigen, antibody combining protein, or antibody.

35 When the first substance is a chemical substance including hydrophobic group such as styrene group, phenyl group, and alkyl group for modifying a base plate surface to

act on the immobilization of the captures onto the base plate by means of hydrophobic bond; the second substance includes at least an amphiphilic substance.

In this case, it is preferable that the first substance includes at least polystyrene or alkylbenzene; and the second substance includes at least gelatin or casein.

It is preferable that the second substance is composed of a substance having water repellency including, for example, silicon or fluorine. In general, the biological substance such as the sample containing the capture is in a form of aqueous solution in many cases. When the substance, which has the water repellency or the hydrophobicity, is selected as the second substance, the effect is further enhanced to inhibit the immobilization of the capture onto the base plate. Further, the sample solution (sample solution containing the specimen), which is employed when the biochip is used, is also in a form of aqueous solution in many cases. In such a situation, the nonspecific binding of the sample to the portions other than the spots is effectively suppressed by the repelling force with respect to the portions at which the second substance is formed other than the spots. Thus, the S/N ratio of the signal of the spot is improved.

It is also preferable that the captures are nucleic acids. In this case, the nucleic acid is exemplified by DNA and/or fragment thereof or amplified product thereof; cDNA and/or fragment thereof or amplified product thereof; RNA or

antisense RNA and/or fragment thereof or amplified product thereof; chemically synthesized DNA or amplified product thereof; or chemically synthesized RNA or amplified product thereof.

5 It is also preferable that the captures are proteins. In this case, the protein is exemplified by antigen, antibody, lectin, adhesin, receptor for physiologically active substance, or peptide.

The above and other objects, features, and advantages of the present invention will become more apparent from the following description when taken in conjunction with the accompanying drawings in which a preferred embodiment of the present invention is shown by way of illustrative example.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating steps of a method for producing a biochip according to a first embodiment;

FIG. 2 is a block diagram illustrating steps as contents of a sample preparation step;

FIG. 3 is a perspective view illustrating the biochip to be produced;

FIG. 4A shows a step illustrating a state in which an immobilization-reinforcing solution is supplied onto a base plate;

FIG. 4B shows a step illustrating a state in which a sample is supplied onto the immobilization-reinforcing



solution on the base plate;

FIG. 4C shows a step illustrating a state in which the sample and the immobilization-reinforcing solution are integrated into one unit;

FIG. 5A is a plan view illustrating an arrangement of a dispenser to be used for the method for producing the biochip according to the first embodiment;

FIG. 5B is a front view thereof;

FIG. 5C is a magnified plan view illustrating one micropipette of the dispenser;

FIG. 6 is a longitudinal sectional view illustrating an arrangement of the micropipette;

FIG. 7 is a perspective view illustrating the shape of a flow passage including a cavity formed in a substrate of the micropipette;

FIG. 8 illustrates an example of the method for producing the biochip by using the dispenser;

FIG. 9A shows a step illustrating a state in which a sample is supplied onto a base plate;

FIG. 9B shows a step illustrating a state in which an immobilization-reinforcing solution is supplied onto the sample on the base plate;

FIG. 9C shows a step illustrating a state in which the sample and the immobilization-reinforcing solution are integrated into one unit;

FIG. 10A shows a step illustrating a state in which an immobilization solution is supplied onto a base plate;

FIG. 10B shows a step illustrating a state in which a sample is supplied onto the immobilization solution on the base plate;

FIG. 11A shows a step illustrating a state in which an immobilization-reinforcing solution is supplied onto a base plate;

FIG. 11B shows a step illustrating a state in which a sample is supplied onto the immobilization-reinforcing solution on the base plate;

FIG. 11C shows a step illustrating a state in which the sample and the immobilization-reinforcing solution are integrated into one unit;

FIG. 12 is a perspective view illustrating a biochip according to a fifth embodiment;

FIG. 13 is a magnified sectional view illustrating the biochip according to the fifth embodiment;

FIG. 14A shows a progress step illustrating a state in which a first substance is formed on an upper surface of a main base plate body;

FIG. 14B shows a progress step illustrating a state in which a second substance is formed at parts other than portions at which spots are to be formed on the first substance;

FIG. 15 shows an example of the method for producing the biochip by using the dispenser;

FIG. 16A shows a progress step illustrating a state in which a resist is formed at a part at which a spot is to be

formed on a first substance formed on the main base plate body;

FIG. 16B shows a progress step illustrating a state in which a second substance is formed on an entire surface including the resist; and

FIG. 16C shows a progress step illustrating a state in which the resist is subjected to lift-off.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Illustrative embodiments of the biochip and the method for producing the same according to the present invention will be explained below with reference to FIGS. 1 to 16C.

At first, as shown in FIG. 1, a method for producing a biochip according to a first embodiment comprises a pretreatment step S1 of forming a poly-L-lysine layer 12 (see FIGS. 4A to 4C) on the surface of a base plate 10, a sample preparation step S2 of preparing a sample containing DNA fragments, a first supply step S3 of supplying (including dropping) an immobilization-reinforcing solution onto the base plate 10, and a second supply step S4 of supplying (including dropping) the sample obtained in the sample preparation step S2 onto the immobilization-reinforcing solution having been supplied onto the base plate 10 to produce the biochip 20 shown in FIG. 3.

As shown in FIG. 2, the sample preparation step S2 includes an amplification step S11 of performing PCR amplification for the DNA fragments to prepare a PCR

product, a powder formation step S12 of drying the obtained PCR product to prepare DNA powder, and a mixing step S13 of dissolving the obtained DNA powder in a buffer solution.

The process will be specifically explained below. That is, in the pretreatment step S1, the base plate 10 is firstly immersed in an alkaline solution to perform slow shaking at room temperature for at least 2 hours. The alkaline solution is a solution which is obtained, for example, by dissolving NaOH in distilled water, and adding ethanol thereto, followed by being agitated until the solution is completely transparent.

After that, the base plate 10 is taken out, and it is transferred into distilled water, followed by being rinsed to remove the alkaline solution. Subsequently, the base plate 10 is immersed in a poly-L-lysine solution prepared by adding poly-L-lysine to distilled water, followed by being left to stand for 1 hour.

After that, the base plate 10 is taken out, and it is applied to a centrifugal machine to perform centrifugation so that any excessive poly-L-lysine solution is removed. Subsequently, the base plate 10 is dried at 40 °C for about 5 minutes to obtain the base plate 10 with the poly-L-lysine layer 12 formed on the surface.

Subsequently, the sample preparation step S2 is performed. At first, 3 M sodium acetate and isopropanol are added to the PCR product amplified by using a known PCR machine (amplification step S11), followed by being left to

stand for several hours. After that, the PCR product solution is centrifuged with a centrifugal machine to precipitate the DNA fragments.

The precipitated DNA fragments are rinsed with ethanol, followed by centrifugation. After that, the DNA fragments are dried to produce the DNA powder (powder formation step S12). A TE buffer solution is added to the obtained DNA powder, followed by being left to stand for several hours to completely dissolve the DNA powder (mixing step S13). Thus, the sample is prepared. The concentration of the sample at this stage is 0.1 to 10  $\mu\text{g}/\mu\text{liter}$ .

In this embodiment, as shown in FIG. 4A, the immobilization-reinforcing solution 16 is supplied onto the base plate 10 (first supply step S3). Subsequently, as shown in FIG. 4B, the sample 14, which is obtained in the sample preparation step S2, is supplied onto the immobilization-reinforcing solution 16 having been supplied onto the base plate 10. Accordingly, the biochip 20 shown in FIG. 3 is produced (second supply step S4). The supply area for the sample 14 is made smaller than the area to which the immobilization-reinforcing solution 16 has been supplied, by adjusting the supply amount. The sample 14 may be diluted depending on the type of the sample 14. Organic polymer is used for the immobilization-reinforcing solution 16. The sample 14 promptly diffused in the immobilization-reinforcing solution 16 after the supply, and the sample 14 is uniformly dispersed in the area prescribed by the

immobilization-reinforcing solution 16 as shown in FIG. 4C.

Especially, in this embodiment, a disperser 30 as shown in FIG. 5A is used for the first supply step S3 and the second supply step S4.

The dispenser 30 has the following arrangement. That is, for example, ten micropipettes 34 are arranged in five rows and two columns on an upper surface of a fixation plate 32 having a rectangular configuration. A group of the micropipettes 34 arranged in the direction of each column are fixed on the fixation plate 32 by the aid of a fixing jig 36 respectively.

As shown in FIGS. 5C and 6, the micropipette 34 comprises a sample-pouring port 52 which is formed at the upper surface of a substrate 50 having a substantially rectangular parallelepiped-shaped configuration, a sample discharge port 54 which is formed at the lower surface of the substrate 50, a cavity 56 which is formed at the inside between the sample-pouring port 52 and the sample discharge port 54, and an actuator section 58 which is used to vibrate the substrate 50 or change the volume of the cavity 56.

Therefore, as shown in FIG. 6, through-holes 40 are provided through the fixation plate 32 at portions corresponding to the sample discharge ports 54 of the micropipettes 34 respectively. Accordingly, the sample 14 or the immobilization-reinforcing solution 16, which is discharged from the sample discharge port 54 of the micropipette 34, is supplied through the through-hole 40,

for example, to the base plate 10 which is fixed under the fixation plate 32.

10  
An introducing bore 60 having a substantially L-shaped configuration with a wide opening width is formed over a region ranging from the sample-pouring port 52 to the inside of the substrate 50 in the micropipette 34. A first communication hole 62 having a small diameter is formed between the introducing bore 60 and the cavity 56. The sample 14 or the immobilization-reinforcing solution 16, which is poured from the sample-pouring port 52, is introduced into the cavity 56 through the introducing bore 60 and the first communication hole 62.

15  
A second communication hole 64, which communicates with the sample discharge port 54 and which has a diameter larger than that of the first communication hole 62, is formed at a position different from that of the first communication hole 62, of the cavity 56. In the embodiment of the present invention, the first communication hole 62 is formed at the portion of the lower surface of the cavity 56 deviated toward the sample-pouring port 52. The second communication hole 64 is formed at the position of the lower surface of the cavity 56 as well corresponding to the sample discharge port 54.

20  
Further, in this embodiment, the portion of the substrate 50, with which the upper surface of the cavity 56 makes contact, is thin-walled to give a structure which tends to undergo the vibration with respect to the external

stress so that the portion functions as a vibrating section 66.

The substrate 50 is constructed by laminating a plurality of green sheets made of zirconia ceramics, followed by being sintered into one unit.

That is, the substrate 50 is constructed by laminating a layer which is formed with a window of the sample-pouring port 52 and which is partially formed with a plurality of windows as a part of the introducing bore 60 and a part of the second communication hole 64 respectively, a layer which is formed with a plurality of windows as a part of the introducing bore 60 and a part of the second communication hole 64 respectively, and a layer which is formed with a window as a part of the second communication hole 64, followed by being sintered into one unit.

The actuator section 58 comprises a base 46 composed of zirconia ceramics constructed by laminating a layer which is partially formed with a plurality of windows as parts of the first communication hole 62 and the second communication hole 64 respectively, a layer which is formed with the cavity 56, and a layer which is provided to form the vibrating section 66, followed by being sintered into one unit in the same manner as in the substrate 50, a lower electrode 70 which is directly formed on the vibrating section 66, a piezoelectric layer 72 which is composed of, for example, a piezoelectric/electrostrictive layer or an anti-ferroelectric layer formed on the lower electrode 70,



and an upper electrode 74 which is formed on the upper surface of the piezoelectric layer 72.

As shown in FIG. 5C, the lower electrode 70 and the upper electrode 74 are electrically connected to an unillustrated driving circuit via a plurality of pads 76, 78 which are formed on the upper surface of the base 46 respectively.

A nozzle sheet 48 is formed with the sample discharge port 54. The sample discharge port 54 is formed through a resin film by means of the excimer laser machining.

The micropipette 34 constructed as described above is operated as follows. That is, when an electric field is generated between the upper electrode 74 and the lower electrode 70, then the piezoelectric layer 72 is deformed, and the vibrating section 66 is deformed in accordance therewith. Accordingly, the volume of the cavity (pressurizing chamber) 56 contacting with the vibrating section 66 is decreased.

When the volume of the cavity 56 is decreased, the sample 14 or the immobilization-reinforcing solution 16 charged in the cavity 56 is discharged at a predetermined speed from the sample discharge port 54 which communicates with the cavity 56. As shown in FIG. 3, it is possible to prepare the biochip 20 in which the sample 14 and the immobilization-reinforcing solution 16 discharged from the micropipettes 34 are aligned and fixed as minute spots 80 on the base plate 50 such as a microscopic slide glass.

1  
2  
3  
4  
5 An apparatus structure based on the so-called ink-jet system may be adopted as the structure in which the volume of the cavity 56 is decreased in accordance with the driving of the actuator section 58 (see Japanese Laid-Open Patent Publication No. 6-40030).

6  
7  
8  
9  
10 The cavity (pressurizing chamber) 56 is formed to have such a flow passage dimension that the sample 14 containing DNA fragments or the like is moved.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
221

54. The sample 14 or the immobilization-reinforcing solution 16 can be introduced to the sample discharge port 54 without disturbing the flow of the sample 14 or the immobilization-reinforcing solution 16 which is moved from the sample-pouring port 52 via the introducing bore 60 and the first communication hole 62 to the inside of the cavity 56.

As shown in FIG. 5A, a plurality of pins 38 for positioning and fixing the micropipettes 34 are provided on the upper surface of the fixation plate 32. When the micropipette 34 is fixed on the fixation plate 32, the micropipette 34 is placed on the fixation plate 32 while inserting the pins 38 of the fixation plate 32 into positioning holes 90 (see FIG. 5C) provided at the both sides of the substrate 50 of the micropipette 34. Thus, a plurality of micropipettes 34 are automatically positioned and aligned with a predetermined array arrangement.

Each of the fixing jigs 36 has a holder plate 100 for pressing the plurality of micropipettes 34 against the fixation plate 32. Insertion holes for inserting screws 102 therein are formed through both end portions of the holder plate 100 respectively. When the screws 102 are inserted into the insertion holes, and they are screwed into the fixation plate 32, then the plurality of micropipettes 34 can be pressed against the fixation plate 32 by the aid of the holder plate 100 at once. One unit is constructed by the plurality of micropipettes 34 which are pressed by one

holder plate 100. As shown in FIG. 5A, one unit is constructed by the five micropipettes 34 which are arranged in the direction of the column.

5 The holder plate 100 is formed with introducing holes 104 (see FIG. 5B) which are used to supply the samples 14 and the immobilization-reinforcing solutions 16 to the portions corresponding to the sample-pouring ports 52 of the respective micropipettes 34 respectively when the plurality of micropipettes 34 are pressed. Tubes 106 for introducing the samples 14 and the immobilization-reinforcing solutions 16 to the introducing holes 104 respectively are held at upper end portions of the respective introducing holes 104.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235  
10240  
1024

sample discharge ports 54 are aligned two-dimensionally. The samples 14 and the immobilization-reinforcing solutions 16 of mutually different types are discharged from the sample discharge ports 54 respectively.

5 In FIG. 5A, the both ends of the holder plate 100 are fixed by being tightened to the fixation plate 20 by the aid of the screws 102. However, the holder plate 100 may be fixed in accordance with other methods based on the mechanical procedure by using, for example, screws and springs, as well as based on an adhesive or the like.

10 As described above, the substrate 50 of the micropipette 34 and the portion of the base 46 of the actuator section 58 are formed of ceramics, for which it is possible to use, for example, fully stabilized zirconia, 15 partially stabilized zirconia, alumina, magnesia, and silicon nitride.

Among them, the fully stabilized/partially stabilized zirconia is adopted most preferably, because the mechanical strength is large even in the case of the thin plate, the 20 toughness is high, and the reactivity with the piezoelectric layer 72 and the electrode material is small.

When the fully stabilized/partially stabilized zirconia is used as the material, for example, for the portion of the base 46 of the actuator section 58, it is preferable that at 25 least the portion (vibrating section 66), on which the piezoelectric layer 72 is formed, contains an additive such as alumina and titania.

Those usable as the piezoelectric ceramics for the piezoelectric layer 72 of the actuator section 58 include, for example, lead zirconate, lead titanate, lead magnesium niobate, lead magnesium tantalate, lead nickel niobate, lead zinc niobate, lead manganese niobate, lead antimony stannate, lead manganese tungstate, lead cobalt niobate, and barium titanate, as well as composite ceramics containing components obtained by combining any of them. However, in the embodiment of the present invention, a material containing a major component composed of lead zirconate, lead titanate, and lead magnesium niobate is preferably used, for the following reason.

That is, such a material has a high electromechanical coupling constant and a high piezoelectric constant. Additionally, such a material has small reactivity with the substrate material during the sintering of the piezoelectric layer 72, making it possible to stably form the product having a predetermined composition.

Further, in the embodiment of the present invention, it is also preferable to use ceramics obtained by appropriately adding, to the piezoelectric ceramics described above, for example, oxides of lanthanum, calcium, strontium, molybdenum, tungsten, barium, niobium, zinc, nickel, manganese, cerium, cadmium, chromium, cobalt, antimony, iron, yttrium, tantalum, lithium, bismuth, and stannum, or a combination of any of them, or other compounds.

For example, it is also preferable to use ceramics

containing a major component composed of lead zirconate, lead titanate, and lead magnesium niobate, and further containing lanthanum and/or strontium.

On the other hand, it is preferable that the upper electrode 74 and the lower electrode 70 of the actuator section 58 are made of metal which is solid at room temperature and which is electrically conductive. For example, it is possible to use metal simple substance of, for example, aluminum, titanium, chromium, iron, cobalt, nickel, copper, zinc, niobium, molybdenum, ruthenium, palladium, rhodium, silver, stannum, tantalum, tungsten, iridium, platinum, gold, and lead, or alloy obtained by combining any of them. Further, it is also preferable to use a cermet material obtained by dispersing, in the metal described above, the same material as that of the piezoelectric layer 72 or the portion of the base 46.

In general, it is preferable that the nozzle sheet 48 is composed of a material suitable for the formation of the discharge port. It is desirable that the nozzle sheet 48 is composed of a resin including, for example, PET, polyimide, polyamide, maleimide, and polysulfone. In order to stably discharge the droplets, it is preferable that the portion, at which the solution is discharged, is subjected to a liquid-repelling treatment with fluororesin or silicon. In the embodiment of the present invention, a silicon-coated PET film, which is excellent in excimer laser machining performance and which is excellent in productivity, can be

preferably adopted.

Further, it is also preferable to use a nozzle sheet composed of a metal sheet such as SUS which is excellent, for example, in drawing machining and punching out based on the use of a die. Also in this case, in order to stably discharge the droplets, it is preferable that the portion, at which the solution is discharged, is subjected to a liquid-repelling treatment with fluororesin or silicon.

Next, explanation will be made in detail below with reference to FIG. 8 for an exemplary method for supplying the sample onto the base plate 10 by using the dispenser 30.

As shown in FIG. 8, a plurality of slide glass base plate 10, for example, twenty glass base plates 10, the surface of each of which is coated with the poly-L-lysine layer 12, are fixed on a glass-fixing jig 110. Subsequently, the immobilization-reinforcing solution 16 is charged into the cavity 56 of each of the micropipettes 34 via the introducing bore 104 of the fixing jig 36 from each of the tubes (not shown) of the dispenser 30 attached to the robot so that the dispenser 30 is freely movable over the glass base plate 10 while controlling the relative position with respect to the glass-fixing jig 110. The actuator section 58 is driven to discharge and supply the immobilization-reinforcing solution 16 onto the base plate 10 as shown in FIG. 4A.

In this procedure, the immobilization-reinforcing solution 16 may be supplied by using all of the ten



micropipettes 34 shown in FIG. 5A. However, the priority is given to the stability of the shape of the supply area, and the supply is performed for the all by using one micropipette 34.

5           Subsequently, another disperser 30 is prepared, in which the interior of the micropipette 34 is previously filled with a substitution solution such as degassed pure water. The sample 14 is poured from the sample-pouring port 52, and then the actuator section 58 is driven to discharge the substitution solution. The interior of the cavity 56 is substituted with the sample 14 from the sample-pouring port 52.

10  
15  
20           At the stage at which the substitution is completed, the actuator section 58 is driven. As shown in FIG. 4B, the sample 14 is discharged and supplied onto the immobilization-reinforcing solution 16 having been supplied onto the base plate 10 set on the same glass-fixing jig. Accordingly, as shown in FIG. 4C, the biochip 20 is produced, in which the sample 14 containing the immobilization-reinforcing solution 16 is supplied onto the base plate 10.

25           Next, explanation will be made below with reference to FIGS. 9A to 11C for other illustrative embodiments of the method for producing biochip according to the present invention.

          As shown in FIGS. 9A to 9C, a method for producing a biochip according to a second embodiment is approximately

the same as the method for producing the biochip according to the first embodiment described above in that the sample 14, the base plate 10, and the dispenser 30 are used in the same manner. However, the former is different from the latter in that the order of supply of solutions onto the base plate 10 is inverted for the immobilization-reinforcing solution 16 and the sample 14.

That is, at first, as shown in FIG. 9A, the sample 14 is firstly supplied. After that, as shown in FIG. 9B, the immobilization-reinforcing solution 16 is supplied in a superimposed manner onto the area to which the sample 14 has been supplied, followed by being integrated into one unit as shown in FIG. 9C.

In the second embodiment, the immobilization-reinforcing solution 16 is required to have such a physical property that the immobilization-reinforcing solution 16 should diffuse in the sample 14 to arrive at the base plate 10. Therefore, it is possible to preferably adopt a monomer or a polymer having a relatively low degree of polymerization.

Next, as shown in FIGS. 10A and 10B, a method for producing a biochip according to a third embodiment is approximately the same as the method for producing the biochip according to the first embodiment described above in that the sample 14, the base plate 10, and the dispenser 30 are used in the same manner. However, the former is different from the latter in that the immobilization

solution 18 is supplied onto the base plate 10, and then the sample 14 is supplied to the area of the immobilization solution 18.

That is, at first, as shown in FIG. 10A, the immobilization solution 18 is firstly supplied onto the base plate 10. After that, as shown in FIG. 10B, the sample 14 is supplied in a superimposed manner onto the area to which the immobilization solution 18 has been supplied.

In the third embodiment, even when the sample 14 is supplied to those other than the area to which the immobilization solution 18 has been supplied, the sample 14 is not immobilized on the base plate 10. A poly-L-lysine solution, which is prepared by adding poly-L-lysine to distilled water, is adopted as the immobilization solution 18.

Next, as shown in FIGS. 11A to 11C, a method for producing a biochip according to a fourth embodiment differs in that the immobilization-reinforcing solution 16 is supplied onto the base plate 10 over an area which includes two or more areas to each of which the sample 14 is to be supplied, and then the sample 14 is supplied thereonto.

That is, at first, as shown in FIG. 11A, the immobilization-reinforcing solution 16 is formed by means of the screen printing method on a substantially entire surface of the base plate 10. Subsequently, as shown in FIG. 11B, the sample 14 is supplied in accordance with the ink-jet method in the same manner as in the embodiments described

above. After that, as shown in FIG. 11C, the immobilization-reinforcing solution 16 and the sample 14 are integrated into one unit to be strongly immobilized on the base plate 10 in the vicinity of the area to which the sample 14 has been supplied.

As described above, in the methods for producing the biochips according to the first to fourth embodiments, the sample 14 containing DNA fragments and the immobilization-reinforcing solution 16 or the immobilization solution 18 for reliably immobilizing the sample 14 are supplied separately from each other to produce the biochip 20. Accordingly, the immobilization is reliably achieved, and the phenomenon, in which minute spots are peeled off, is extremely decreased.

Further, it is unnecessary to provide the step of mixing the sample 14 and the immobilization-reinforcing solution 16 or the immobilization solution 18. Further, it is enough to use a slight amount of the immobilization-reinforcing solution 16 or the immobilization solution 18 required to immobilize the minute amount of the sample 14 supplied onto the base plate 10. Therefore, it is possible to greatly decrease the amount of the immobilization-reinforcing solution 16 or the immobilization solution 18, which is advantageous to simplify the production steps and reduce the cost.

Further, it is unnecessary that the sample discharge port 54 of the dispenser 30 for supplying the

immobilization-reinforcing solution 16 or the immobilization solution 18 is conformed to the supply specification for the sample 14. The sample discharge port 54 can be designed exclusively for the immobilization-reinforcing solution 16 or the immobilization solution 18 (for example, to have a structure to scarcely suffer from drying). Thus, it is possible to improve the degree of freedom of the design.

Further, the sample 14 is not solidified during the supply. Therefore, the sample 14 and the immobilization-reinforcing solution 16 or the immobilization solution 18 can be supplied with enough time margin. Accordingly, the sample 14 and the immobilization-reinforcing solution 16 or the immobilization solution 18 can be supplied while considering, for example, the positioning of the supply portion, the supply timing depending on the type of the sample 14, and the supply amount. It is possible to improve the quality of the biochip 20 and improve the yield.

Next, as shown in FIG. 12, a biochip 110 according to a fifth embodiment comprises a large number of spots 180 based on samples containing captures, the spots 180 being arranged on a base plate 112 by supplying, onto the base plate 112, a plurality of types of the samples containing captures to be used to specifically react with a specimen in order to obtain information on a structure or a function of the specimen.

As shown in FIG. 13, the base plate 112 comprises a main base plate body 114 which is composed of, for example,

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

a microscopic slide glass, a first substance 116 which is formed on the upper surface of the main base plate body 114 and which acts on the immobilization of the capture onto the base plate 112, and a second substance 118 which is formed at parts other than portions at which the spots 180 are to be formed on the first substance 116 and which inhibits at least the immobilization of the capture onto the base plate 112.

Especially, the second substance 118 is composed of a substance which inhibits the immobilization of the capture onto the base plate 112 and which inhibits the contact of the specimen with the base plate 112.

In this case, the capture includes, for example, nucleic acids and proteins. The nucleic acid includes DNA and/or fragment thereof or amplified product thereof; cDNA and/or fragment thereof or amplified product thereof; RNA or antisense RNA and/or fragment thereof or amplified product thereof; chemically synthesized DNA or amplified product thereof; and chemically synthesized RNA or amplified product thereof.

On the other hand, the protein includes, for example, antigen, antibody, lectin, adhesin, receptor for physiologically active substance, and peptide.

Next, the first substance 116 and the second substance 118 will be explained. At first, when the first substance 116 is a chemical substance having positive charge to act on the immobilization of the captures on the base plate by

means of ionic bond, the second substance 118 is a chemical substance having negative charge.

In this case, the first substance 116 is a silane coupling agent such as  $\gamma$ - $\gamma$ -aminopropyltriethoxysilane, poly-L-lysine, polyethyleneimine, or polyalkylamine, and the second substance 118 is succinic acid or polyacrylic acid.

When the first substance 116 is a chemical substance having an active group for modifying the surface of the base plate 112 to act on the immobilization of the captures onto the base plate 112 by means of covalent bond by effecting a chemical reaction of the active group introduced into the surface of the base plate 112 and a functional group introduced by modifying the captures, the second substance 118 is a chemical substance having the functional group reactive with the active group.

In this case, the chemical reaction to achieve the covalent bond is a reaction of amino group and aldehyde group, a reaction of amino group and N-hydroxysuccinimido group, a reaction of amino group and carboxyl group, a reaction of amino group and epoxy group, or a reaction of thiol group and epoxy group.

In such a case, the first substance 116 is a mixture of  $\gamma$ -aminopropyltriethoxysilane and glutaraldehyde, a mixture of  $\gamma$ -aminopropyltriethoxysilane, succinic anhydride, and N-hydroxysuccinimido, a mixture of  $\gamma$ -aminopropyltriethoxysilane and succinic anhydride, epichlorohydrin, or bisoxysilane, and the second substance

118 is glycine as amino acid, tris having amino group, ethanolamine, cysteine having thiol group, glutathione, or thioglycol.

5 When the first substance 116 is a chemical substance for modifying the surface of the base plate 112 to act on the immobilization of the captures onto the base plate 112 by means of affinity bond, the second substance 118 is a substance which makes the affinity bond with the same chemical substance as the capture.

10 In this case, the first substance 116 is avidin, streptavidin, protamine, histone, biotin, antigen, antibody combining protein, or antibody, and the second substance 118 is avidin, streptavidin, biotin, nucleic acid, antigen, antibody combining protein, or antibody.

15 When the first substance 116 is a chemical substance including hydrophobic group such as styrene group, phenyl group, and alkyl group for modifying the surface of the base plate 112 to act on the immobilization of the captures onto the base plate 112 by means of hydrophobic bond, the second substance 118 is an amphiphilic substance.

20 In this case, the first substance 116 is polystyrene or alkylbenzene, and the second substance 118 is gelatin or casein.

25 Alternatively, the second substance 118 is a resin containing silicon or fluorine for all of the first substances 116 referred to above. The resin containing silicon or fluorine has liquid repellency with respect to



the aqueous solution. Therefore, an effect is also obtained such that the sample solution itself is repelled during the use of the biochip, in addition to the fact that the resin containing silicon or fluorine effectively prevents the first substance from contact with the base plate to avoid immobilization thereof. The background noise with respect to the spot signal has been reduced to be not more than 1/2.

Next, explanation will be made with reference to FIGS. 14 to 16C for a method for producing the biochip 110 according to the fifth embodiment.

At first, as shown in FIG. 14A, the first substance 116 is formed on the entire surface of the main base plate body 114 by means of, for example, the screen printing method. Of course, it is also allowable to use, as the main base plate body 114, one in which the first substance 116 is previously formed on the upper surface.

Subsequently, as shown in FIG. 14B, the second substance 118 is supplied by means of the ink-jet system to parts other than the portions at which the spots 180 are to be formed on the first substance 116 formed on the main base plate body 114.

The second substance 118 can be supplied by the ink-jet system by using the dispenser 30 as shown in FIG. 5A in the same manner as in the embodiment described above.

Especially, as described later on, the dispenser 30 is also used when the sample containing the capture is supplied onto the base plate 12. In this case, the cavities 56 of

the respective micropipettes 34 are filled with the samples containing the captures. The samples in the cavities are discharged at the predetermined speed from the sample discharge ports 54 communicating with the cavities 56, in accordance with the decrease in volumes of the cavities 56. The samples discharged from the micropipettes 34 are supplied onto the base plate 112 as shown in FIG. 12. Thus, the biochip 110, in which the samples are aligned and immobilized as the spots 180, is produced.

The cavity (pressurizing chamber) 56 of each of the micropipettes 34 is formed to have such a flow passage dimension that the sample or the second substance 118 described above is moved therethrough. The cavity 56 is preferably made of a material of ceramics having good affinity with respect to the second substance 118 and the sample.

Next, explanation will be made in detail below with reference to FIG. 15 for an exemplary method for supplying the second substance 118 and the sample onto the main base plate body 114 by using the dispenser 30.

As shown in FIG. 15, a plurality of main glass base plate bodies 114, for example, twenty main glass base plate bodies 114, the surface of each of which is formed with the first substance 116, are fixed on a glass-fixing jig 210. Subsequently, the second substance 118 is charged into the cavity 56 of each of the micropipettes 34 via the introducing bore 104 of the fixing jig 36 from each of the

tubes (not shown) of the dispenser 30 attached to the robot so that the dispenser 30 is freely movable over the main glass base plate body 114 while controlling the relative position with respect to the glass-fixing jig 210. The actuator section 58 is driven to discharge and supply the second substance 118 onto the parts other than the portions at which the spots 180 are to be formed on the first substance formed on the main base plate body as shown in FIG. 14B.

In this procedure, the second substance 118 may be supplied by using all of the ten micropipettes 34 shown in FIG. 5A. However, the priority is given to the stability of the shape of the supply area, and the supply is performed for the all by using one micropipette 34.

Subsequently, another disperser 30 is prepared, in which the interior of the micropipette 34 is previously filled with a substitution solution such as degassed pure water. The sample 14 containing the capture is poured from the sample-pouring port 52, and then the actuator section 58 is driven to discharge the substitution solution. The interior of the cavity 56 is substituted with the sample 14 from the sample-pouring port 52.

At the stage at which the substitution is completed, the actuator section 58 is driven. As shown in FIG. 13, the sample 14 is discharged and supplied to the part at which the spot 180 is to be formed, i.e., to the part at which the first substance 116 is exposed, on the main base plate body

114 set on the same glass-fixing jig 210. Accordingly, as shown in FIG. 12, the biochip 110 is produced, in which the large number of spots 180 based on the samples 14 are arranged on the base plate 112.

5 As described above, in the biochip 110 and the method for producing the same according to the fifth embodiment, the first substance 116, which acts on the immobilization of the capture onto the base plate 112, is formed on the entire surface of the main base plate body 114. The second substance 112, which inhibits the immobilization of the capture onto the base plate 112 and which inhibits the contact of the specimen with the base plate 112, is formed at the parts other than the portions at which the spots 180 are to be formed on the first substance 116 having been formed on the main base plate body 114. Therefore, the shape and the arrangement form of the spots 180 are determined by the shape of the parts at which the second substance 118 is not formed.

10  
15  
20 Accordingly, for example, inconveniences, in which the arrangement spacing between the spots 180 is dispersed and the spots 180 are putted close to one another, disappear when the samples are supplied onto the base plate 112. Further, when the sample cannot be supplied to the prescribed position, the sample is prevented from contact with the base plate 112 owing to the presence of the second substance 118. Therefore, no contamination source is generated.

25

Further, splashes or mists, which are caused by the satellite phenomenon often caused during the discharge of the sample when the sample is supplied in accordance with the ink-jet system, are prevented from contact with the base plate 112 owing to the presence of the second substance 118. Therefore, it is possible to dissolve the problem of satellite having been hitherto caused by the ink-jet system.

That is, in the fifth embodiment, it is possible to inexpensively obtain the high quality biochip 110. It is possible to simplify the production steps, reduce the cost, and improve the yield of the biochip 110.

The fifth embodiment described above is illustrative of a case in which the second substance 118 is supplied in accordance with the ink-jet system by using the dispenser 30. Alternatively, the second substance 118 may be formed in accordance with the screen printing method. In this case, it is possible to shorten the time required to supply the second substance 118 to the parts other than the portions at which the spots 180 are to be formed. It is possible to improve the throughput and reduce the number of steps.

As another alternative method, the second substance 118 may be formed in accordance with the dipping method. In this case, for example, as shown in FIG. 16A, a resist 212 is formed at portions at which the spots 180 are to be formed on the first substance 116 having been formed on the main base plate body 114. After that, as shown in FIG. 16B,

the second substance 118 is formed in accordance with the dipping method over the entire surface including the resist 212. After that, as shown in FIG. 16C, the resist 212 is subjected to lift-off. Accordingly, the second substance 118 is formed at the parts other than the portions at which the spots 180 are to be formed.

The method based on the dipping is preferred when the second substance 118 has a low viscosity. Also in this case, it is possible to shorten the time required to supply the second substance 118 to the parts other than the portions at which the spots 180 are to be formed. It is possible to improve the throughput and reduce the number of steps.

It is a matter of course that the biochip and the method for producing the same according to the present invention are not limited to the embodiments described above, which may be embodied in other various forms without deviating from the gist or essential characteristics of the present invention.